

SPIT PULSA 800E



+ Pulsa E-Lift
pole tool



In accordance to:
EN 12549
EN ISO 11148-13
Directive tool :
2006/42/EC
2011/65/UE
1999/5/EC
CEM 2004/108/EC
Fuel cell : 75/324/EC
Battery : 2006/66/EC
Charger :
2006/95/EC
CEM 2004/108/EC

Tool specifications

Name	SPIT PULSA 800E
Impact force (Joules)	82
Weight (kg)	3.7 kg (with battery)
Overall dimension LxHxW (mm)	385x114x309
Energy	Fuel cell & Battery
Fastener lengths (mm)	15 to 40 mm in strip

Characteristics

Electrical accessories pin-guide
Fully automatic tool (1000 shots per hour)
20 pins magazine (10 per strip)
Gas & Battery gauges: check gas & battery levels anytime
Start & Go system: energy saving, "self cut-off" when it is not used for 1mn
Low push down force (4.5 kg)
Automatic energy absorber
Automatic gas dosage (used T° - 15 °C to + 49 °C)
Battery charging time: 90 mn (25 mn = 500 pins)
Fuel cell: 750 shots (20 °C), battery: up to 3000 shots

Safety specifications

CE marking
Complete tool pressure necessary to generate the shot
Security with on / off led indicator
Noise level, EN 12549 : LpA,1s,1m=96dB(A) / Lp Cpeak=135 dB(C)
Vibration, EN ISO 8662-11: 4.1 m·s ⁻²

Accessories	Consumables
50 pins magazine WARNING: incompatible with Pulsa lift	C6, HC6, CG6, CT-CLIP, E-CLIP, E-CAV, CLIPELEC, ...TRH-CLIP
Magnetic pin guide	Metal P-CLIP
Cleaning kit	
Pulsa E-LIFT pole tool	