

SPIT PULSA 800P+



In accordance to:
 EN 12549
 EN ISO 11148-13
 Directive tool :
 2006/42/EC
 2011/65/UE
 1999/5/EC
 CEM 2004/108/EC
 Fuel cell : 75/324/EC
 Battery : 2006/66/EC
 Charger :
 2006/95/EC
 CEM 2004/108/EC

Tool specifications

Name	SPIT PULSA 800P+
Impact force (Joules)	100
Weight (kg)	3.7 (with battery)
Overall dimension LxHxW (mm)	396x114x309
Energy	Fuel cell & Battery
Fastener lengths (mm)	15 to 40 mm in strip

Characteristics

Drywall pin guide
Fully automatic tool (1000 shots per hour)
20 pins magazine (10 per strip)
Low push down force (4.5 kg)
Gas & Battery gauges: check gas & battery levels anytime
Start & Go system: energy saving, "self cut-off" when it is not used for 1mn
Automatic gas dosage (used T° - 15 °C to + 49 °C)
Battery charging time: 90 mn (25 mn = 500 pins)
Fuel cell: 600 shots (20 °C), battery: up to 3000 shots

Safety specifications

CE marking
Complete tool pressure necessary to generate the shot
Security with on / off led indicator
Noise level, EN 12549 : LpA,1s,1m=95dB(A) / Lp Cpeak=135 dB
Vibration, EN ISO 8662-11: 4.4 m·s ⁻²

Accessories	Consumables
50 pins magazine	C6, HC6, CW6
Magnetic pin guide	Metal washer
Cleaning kit	